

BE IT KNOWN that I, *Uwe HASLER*, have invented certain
new and useful improvements in

METHOD FOR ADJUSTING A TREATMENT MACHINE

of which the following is a complete specification:

BACKGROUND OF THE INVENTION

The present invention relates to a method for adjusting a treatment machine, in particular a bottle cleaning machine.

5 More particularly, it relates to a method of adjusting a treatment machine, in which a transporting chain provided for transportation of objects to be treated is guided in loops, in particular meanderingly, through one or several treatment stations in a machine housing and is driven at least at two locations by a drive, so that in a normal operation they are synchronized and adjusted relative to one another, so that the transporting chain in its guides is neither over tightened nor compressed.

10 Such treatment machines are known in particular as bottle cleaning machines. In such bottle cleaning machines bottles are guided in bottle carriers through the cleaning stations of the machine. The machine has individual holders arranged in a horizontal row for receiving of the bottles, which are mounted with their ends on chain members of the roller chains. The roller chains are guided by guiding rails and folded meanderingly in a vertical plane in the machine housing. In order to maintain friction losses, chain forces and wear within certain limits, the transporting chains of known flat cleaning machines are driven at several locations. This is usually performed by means of horizontal and mutually parallel drive

15

20

shafts, on which each corresponding chain pair is arranged for engaging in the transporting chain. Typically two-eight drive shafts are provided.

5 These drive shafts must be driven synchronously, so that the transporting chain is not subjected between two successive drive shafts to significant and usually disadvantageous pressing and pulling forces. Otherwise, the transporting chain and its guiding rails can be damaged or prematurely worn out. The synchronization of the drive shafts can be provided by mechanical means with shafts, transmissions, or chains, or by an electronic synchronous regulation, when several drive motors are provided for each drive shaft or each group of drive shafts.

10 A chain gap must be adjusted between two drives arranged successively in a pulling direction of the transporting chain so that the transporting chain is guided not too loosely and not too tightly. For adjusting the desired chain gap, the relative rotary position of the successive drive shafts is changed. When the synchronization of the drives is performed by mechanical means, the chain gap can be adjusted by displacement of couplings or chain drives. With electronic synchronization, the angular position of the neighboring drives can be changed by the asynchronous actuation of the individual drives.

SUMMARY OF THE INVENTION

Accordingly, it is an object of the present invention to provide an improved method for adjusting treatment machine, which is substantially automated and can be performed in a simple manner without trained and experienced personnel.

In keeping with these objects and with others which will become apparent hereinafter, one feature of present invention resides, briefly stated, in a method which has the following steps.

- a. Two drives which follow one another in a forward direction of the transporting chain are selected;
- b. The selected drives are driven asynchronously so that they tightly pull or compress the chain portion located between them by producing a length difference, and a parameter which is dependent from the drive moment of one or both drives is measured;
- c. When the parameter reaches or exceeds a fixed value, the drives are driven asynchronously in direction of a reduction of the previously produced length difference by a predetermined amount;

- d. The so adjusted relative position of the both drives with respect to one another is subsequently maintained, in particular during the synchronous operation of the drives;
- e. The preceding method steps are used for further drives until the chain lengths are adjusted in all portions to be adjusted.

The inventive method has the advantage that it is composed of simple method steps, which are performed in dependence on simple parameters. For its performance, no trained or experienced personnel is needed. It can be performed automatically in a simple manner. The method is simple and reliable since special measuring devices on or in the machine, for example for measurements of the chain tensioning and position are dispensed with.

The predetermined value for the parameter which is dependent from the drive motor is determined so that the corresponding drive moment substantially exceeds a drive moment which is sufficient for tightening of the corresponding chain portion and nevertheless is not so great that a component of the treatment machine, in particular the transporting chain or the drive motor can be unpermissibly loaded. The amount determined for the reduction of the previously produced length difference is selected so that the chain portion to be adjusted sits in its guides not too loosely and not too tightly.

The method is preferably performed outside of the normal operational time, in particular when the treatment machine is maintained at certain times. Basically the method can be performed also during the normal operation, by driving of two drives arranged one after the other in the pulling direction with insignificantly different speeds and forming a parameter which is used for the indication of the tightly pulled or compressed chain portion, for example from the difference between the drive moments of the both drives. During the operation of the treatment machine, the transporting chain, due to wear and pull load, becomes longer after a certain time. Since it is an endless chain, conventionally in a treatment machine a portion is provided for the receipt of the thusly produced excessive chain length. In particular, the transporting chain is suspended so that it more or less sags in form of a loop. It is to be understood that the inventive method is not performed with two drives which are arranged before and after such a compensating portion.

In accordance with another embodiment of the inventive method for a treatment machine with a compensation portion, it is provided that the drive direction of the drive between the chain portion to be adjusted and the compensation portion together with a selected drive and/or all remaining drives together with the other selected drive are operated synchronously. This feature guarantees that for example during a tight pulling of the individual chain portions the neighboring chain portion is not compressed or vice versa. When as provided, all preceding or all

subsequent drives are operated synchronously, such a compression in the neighboring chain portions, which can produce an additional counter moment with falsified the measuring results, is prevented with a corresponding advantage. In known treatment machines, as a rule, all chain portions between each two drives are designed differently with respect to their length and the geometric shape of their guides. In this case, it is especially advantageous when for each chain portion to be adjusted, a special parameter which depends on the drive moment is provided, since the optimal chain adjustment must be provided in general in each chain portion with another drive moment.

The same is true for the amount, by which the drive after reaching of a predetermined drive moment must be "adjusted back". In accordance with a further embodiment of the inventive method, it is provided that for each chain portion to be adjusted, a special predetermined amount for the reduction of the previously obtained length difference is provided.

An accurate adjustment of the corresponding chain portion can be also provided when not only the tightly pulled or compressed condition of the chain portion is determined, but also when both conditions are determined. In a variant of the inventive method it is therefore provided that in the frame of the method steps b and c the chain portion to be adjusted is tightly pulled first for obtaining a first parameter value, and then with

5 registration of the chain length which is required for it, is compressed until it reaches a second parameter value, or vice versa, and the amount of the subsequent adjustment step depends on the register chain length. The adjustment step is also not strictly predetermined from the tightly pulled or compressed adjustment, but instead it depends on the length difference of the chain portion between the compressed and the tightly pulled position, or in other words from both positions.

10 In accordance with a preferable embodiment of the present invention, the drives are controllable electrically, and the method is performed automatically by means of a microprocessor which is programmed in a suitable way. A programmable microprocessor provides nowadays the simplest, multi-facet and cost-favorable possibility for realization of an automatic control. In this case, it is especially advantageous when the drives are provided with rotary sensors for determination of their relative angular positions, the angular positions are stored, and the synchronization is performed from electrical path via the control of the drive. Such an electrical synchronization, requires in particular during the use of a programmable microprocessor, only a small expense without expensive mechanical components.

20 The inventive method can be performed particularly simple and cost favorable when the drives have electric motors whose current

consumption is measured as a drive moment-dependent parameter. In this embodiment, no additional sensors are needed for the measurement of the drive moment. Also, when the invention is described here in connection with the rotatable electric motors, such drives also can include electric linear motors. In this case, the terms rotary angle and drive moment must be replaced with the terms displacement and drive force.

In accordance with a preferable embodiment of the inventive method which is characterized by a particularly simple control process, an electrical drive which is arranged first in a forward direction of the transporting chain after the compensating portion and the chain portion to be adjusted is determined, and the subsequently arranged second electrical drive, are operated synchronously with all subsequent drives in the forward direction, until its current consumption exceeds a predetermined value. Then the second drive together with all subsequent drives are stopped, turned back by a predetermined rotary angle opposite to the forward direction and subsequently fixed, the method is proceeded with the third and all subsequent drives correspondingly until the last chain portion arranged before the compensation portion is adjusted. For the case when the available drive control does not allow return operation of the drive, another method is recommended which also has an especially simple control course. This method starts as the above described method, however after the first stop of the second drive, the first drive is turned by a predetermined rotary

angle in the forward direction and subsequently is fixed together with the second drive. The method is proceeded with the third and all subsequent drives correspondingly, until the last chain portion arranged before the compensation portion is adjusted, and before the chain portion to be adjusted and after the arranged drive it is operated correspondingly synchronously or together.

In accordance with a further embodiment of the invention, the inventive method provides in addition to a correct chain adjustment also a value of the chain elongation required for the normal operation of the treatment machine in running, and thereby the connected chain wear.

In accordance with a further method it is provided that the chain length difference occurring in each adjustment is measured and stored, and their sum is evaluated as an indicator for the total chain elongation average and/or the chain wear. It is to be understood that in a treatment machine with a compensating portion for the chain leg also a modified method can be used, in which the length of the chain sagging is measured in the compensating portion and an indicator for the total chain length and/or chain wear is evaluated.

The novel features which are considered as characteristic for the present invention are set forth in particular in the appended claims. The

invention itself, however, both as to its construction and its method of operation, together with additional objects and advantages thereof, will be best understood from the following description of specific embodiments when read in connection with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The single figure of the drawing is a view schematically showing a bottle cleaning machine in accordance with the present invention in a vertical direction.

DESCRIPTION OF PREFERRED EMBODIMENTS

5 The drawing shows a machine housing 1 in which a closed transporting chain 2 is guided in meandering loops. The transporting chain 2 has a great number of bottle carriers 3 which are arranged in a pulling direction one after the other and in a horizontal direction, or in other words perpendicular to the plan of the drawings in rows one near the other. A bottle feeding device 4 provides in a fast sequence a complete row of the bottle carriers 3 in the forward direction 5 with bottles to be cleaned. The transporting chain 2 transport the bottle carriers 3 with the bottles through different treatment stations 6, where they are rinsed with different fluids and cleaned. The cleaned bottles are removed from the bottle carriers 3 by a bottle discharge device 7. The empty bottle carriers 3 then are moved back, and shortly before the bottle feeding device 4 a compensation portion 8 is provided. During the operation it takes up excessive chain lengths produced by wear and pulling action, in form of a variable chain sagging.

10 For driving the transporting chain 2, separate drives 9, 10, 11, 12, 13, 14 are provided. They are composed of drive shafts which are driven by a not shown electric motor and have a chain sprocket pair engaging the transporting chain 2. The electric motors are synchronized with one another by a not shown electrical control. The control is performed at best by a programmable small computer. The angular positions of the drives 9-14 are

measured by rotary sensors and their relative positions with respect to one another are stored for synchronization of the drives 9-14. With to the synchronous drive it is guaranteed that the transporting chain 2 is not tightly pulled or compressed in its guides 15.

5

In order to adjust the chain in accordance with the present invention, first two drives are selected. Preferably the selected drives include a first drive 9 which is arranged in the forward direction 5 of the transporting chain after the compensating portion 8 and the first chain portion 16 to be adjusted and a subsequent drive 10 in the forward direction 5. The selected drives 9 and 10 are driven asynchronously. In particular, the first drive 9 is fixed and the second drive 10 is driven in the forward direction 5. Together with the second drive 10, also the subsequent drives 11-14 are driven in the forward direction, so that the transporting chain 2 in the subsequent chain portions 17-20 are neither tightly pulled nor compressed.

15

When the drive 10 is driven in the forward direction 5, its current consumption is measured as a measure for the used drive moment. By feeding of the transporting chain 2 by the drive 10 with the simultaneously fixed drive 9, a length difference is produced which leads to tight pulling of the chain portion 16 until it fixedly lies on its corresponding guides 15.

When the current consumption of the drive 10 exceeds a predetermined value, all drives 10-14 are stopped and subsequently turned back over a predetermined rotary angle opposite to the forward direction 5, and the rotary angle in the drive 10 is measured.

5

The predetermined value for the current consumption is naturally determined so that the corresponding drive moment is greater than a drive moment sufficient for tightening of the corresponding chain portion and is smaller than a drive moment which can be damaging for the machine in a corresponding component. The predetermined rotary angle is determined so that the chain portion of the transporting chain 2 to be adjusted sits in its guides 15 neither too loose nor too tight.

Alternatively, with fixed drives 10-14 the drive 10 can be turned over a predetermined rotary angle in the forward direction 5. This second possibility is suitable for example for machines, whose drives can not be operated or can be operated with great difficulties opposite to the forward direction 5.

When now the desired chain length is adjusted in the first chain portion 16, the inventive method provides adjustment of the second chain portion 17, in that on the one hand the drives 9 and 10 and on the other hand the drives 11-14 are synchronously coupled with one another.

First the drives 9 and 10 are stopped and the drives 11-14 are driven together in the forward direction 5, until the chain portion 17 firmly abuts against its drives 15 and until the current consumption of the drive 11 exceeds a predetermined value, which depending on the demand can exceed the value provided for the adjustment of the proceeding chain portions 16 or all subsequent chain portions 18-20.

Now all drives 11-14 are stopped, and subsequently operated over a predetermined rotary value measured at the drive 11, opposite to the forward direction 5. This rotary angle can be also different from the rotary angle provided for the adjustment of the preceding chain portion 16 or all subsequent chain portions 18-20.

As an alternative for turning the drives 11-14 back, it is to be understood that both drives 9 and 10 can be turned together synchronously in the forward direction over the predetermined rotary angle.

After the adjustment of the chain portions 17, in a corresponding continuation of the process the chain portion 18 follows. The drives 9-11 are fixed and the drives 12-14 are driven for tightening of the chain portion 18. The method ends after the adjustment of the last chain portion 20, with the drives 9-13 fixed and the drive 14 is driven alone in the forward direction 5 until the chain portion 20 firmly lies on its guides 15. The

last method step is performed after the current consumption of the drive 14 exceeds a predetermined value. The drive 14 is turned back in this case over a predetermined rotary angle, or as alternative, all drives 9-13 are turned together synchronously over a predetermined rotary angle in the forward direction 5.

The excessive chain length which is produced by elongation or wear of the transporting chain 2, is supplied in the inventive process into the compensation portion 8 and contributes there to a greater sagging of the transporting chain 2. The length of the chain sagging can be measured as an indicator for the chain wear, and in the event of exceeding a fixed chain length, a maintenance of the bottle cleaning machine is performed before it can lead to unpredictable and costly failures.

When the bottle cleaning machine is however controlled by a programmable microprocessor, a special measurement of the chain sagging can be dispensed with. In particular, chain length differences occurring during each adjustment can be measured during the adjustment and stored. Their sum can be evaluated as an indicator for the total chain length and thereby the chain wear. This can be provided in particular in that the relative rotary angle of the second drive arranged in a sequence before and after the adjustment of the enclosed chain portion can be determined, and the angle difference calculated and stored.

For example the drives 9 and 10 before the adjustment of the first chain portion are driven always synchronously, so that their both rotary angles are fixedly coupled. During the adjustment of the chain portion 16, this coupling is removed and a relative displacement of the angular positions occurs by an amount which is dependent from the length of the chain portion 16. After the adjustment the both drives 9 and 10 are again coupled synchronously with one another, while however the relative angular position of the drive 9 to the angular position of the drive 10 is changed by an angle difference. The angle difference is stored similarly to the angle differences which occur during the adjustment of the subsequent chain portions 17-20. The sum of all angle differences is then added to the total sum of the angle differences from other method steps. This total sum is a measure for the total chain length and thereby for the chain wear.

The inventive method can be performed completely automatically, in particular, by controlling with a programmable microprocessor, for example outside of the normal operational type of the bottle cleaning machine. Basically, the method can be performed also during the normal operation of the bottle cleaning machine.

In this case, the synchronously running drives 9-14 are subdivided into two synchronously running groups. When for example the chain portion 18 must be adjusted, on the one hand the drives 9-11 and on

the other hand the drives 12-14 are driven synchronously with one another. The electrical control increases for example the rotary speed of the drives 12-14 which are coupled with one another and thereby a displacement of the relative rotary angle with respect to the drives 9-11 which are operated being coupled with one another.

The rotary angle difference can be determined in a simple manner in that, a rotary angle which is read by the rotary sensor of the drive 12 is evaluated positively and the rotary angle determined by the rotary sensor of the drive 11 is evaluated negatively. In particular when the rotary angle is provided digitally or as a pulse sequence, the subtraction can be performed in a simple manner. For example an electronic forward/rearward counter which counts the pulses supplied by the rotary sensor of the drive 12 forwardly and counts the pulses supplied by the rotary sensor of the drive 11 rearwardly can be used. The counter content is always composed of a count which is proportional to the rotary angle difference.

With these steps, the chain portion 18 is straightened and fixedly lies on its guides 15. This leads to an increased friction and thereby to an increased current consumption of the drive 12. When now for example the current consumption of the drive 12, the drive 11 or its sum or difference exceeds a predetermined value, the angle difference is stored and thereafter the coupled drives 12-14 are driven with lower speed, until the angle

difference for the group of the drives 9-11 is reduced by a predetermined amount. Now the chain length of the chain portion 18 is properly adjusted, and all drives 9-14 are again synchronized with one another. After this, the method can continue with each other chain portion, until it is finished.

5

It will be understood that each of the elements described above, or two or more together, may also find a useful application in other types of constructions differing from the types described above.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216

- 1 d. Subsequently maintaining the adjusted relative position of the
2 both drives relative to one another, with asynchronous
3 operation of the drives; and
4 e. using the preceding steps for further drives, until chain lengths
5 in all chain portions to be adjusted are adjusted.

- 1 2. A method as defined in claim 1; and further comprising the
2 step of operating synchronously a drive arranged in a drive direction between
3 a chain portion to be adjusted and a compensating portion of the transporting
4 chain for receiving an excessive chain length, together with a selected drive
5 and/or all remaining drives together with the other selected drive.

- 1 3. A method as defined in claim 1; and further comprising
2 providing a parameter which is ^{dependent} independent from the drive moment, for each
3 chain portions to be adjusted.

1 4. A method as defined in claim 1; and further comprising
2 providing a special predetermined amount for a reduction of the previously
3 produced length difference for each chain portion to be adjusted.

1 5. A method as defined in claim 1; and further comprising, first
2 pulling tight the chain portion adjusted in the steps b and c until reaching a
3 first parameter, and then with registering the chain lengths which is required
4 for it, compressing the chain portion until reaching a second parameter value
5 or vice versa; and providing an amount of subsequent adjusting steps in
6 dependence on the registered chain length.

1 6. A method as defined in claim 1; and further comprising
2 electrically controlling the drives; and performing the method automatically
3 by a programmable microprocessor.

1 7. A method as defined in claim 6; and further comprising
2 providing the drives with rotary sensors for determination of their relative

1 angular positions; storing the angular positions; and performing the
2 synchronization of an electrical path by controlling the drives.

forming

1 8. A method as defined in claim 1; and further comprising
2 providing the drives with electric motors; and measuring current consumption
3 of the electric motors as parameters which are dependent from drive
4 moments.

1 9. A method as defined in claim 1; and further comprising
2 forming the drives as electrical drives; fixing a first electrical drive arranged
3 in the forward direction of said transporting chain after a compensation
4 portion and before a chain portion to be adjusted; operating a subsequently
5 arranged second electrical drive synchronously with all subsequent electrical
6 drives in the forward direction until its current consumption exceeds a
7 predetermined value; then stopping the second drive together with all
8 subsequent drives, turning them back by predetermined rotary angle
9 opposite to the forward direction, and subsequently stopping; continuing the
10 method with a third and subsequent drives correspondingly until a last chain
11 portion arranged before the compensation portion is adjusted.

1 10. A method as defined in claim 1; and further comprising
2 forming the drives as electrical drives; fixing a first electrical drive arranged
3 in the forward direction of said transporting chain after a compensation
4 portion and before a chain portion to be adjusted; operating a subsequently
5 arranged second electrical drive in the forward direction until its current
6 consumption exceeds a predetermined value, stopping the second drive
7 together with subsequent drives and turning the first drive by a
8 predetermined rotary angle in the forward direction, and subsequently fixing
9 it together with said second drive; continuing the method with a third and all
10 subsequent drives until a last chain portion arranged before the
11 compensation portion is adjusted; and operating the chain portions adjusted
12 previously and the drives arranged after synchronously or fixing them
13 together.

1 11. A method as defined in claim 1; and further comprising
2 measuring chain length differences occurring during each adjustment; storing
3 the measured chain length differences; and evaluating their sum as an
4 indicator for a total chain length and/or chain wear.

1 12. A method as defined in claim 11; and further comprising
2 measuring a length of a chain sagging in a compensation portion and
3 evaluating it as an indicator for a total chain length and/or chain wear.

1 13. A method as defined in claim 1; and further comprising
2 using a programmable control for performing the adjustment.

add B3